

Technical Data Sheet

Polyvinyl Acetate

Specifications:

Type:	Low MW	Mid MW	High MW
Viscosity (10% Ethyl Acetate) 20°C mPa.s	1.0-1.8	2.0-2.8	3.0-3.8
Softening point (Ring & Ball) °C	90-110		
Lead (ppm) max	1		
As (ppm) max	3		
Heavy metals (ppm) max	10		
Volatile matter % max	2.0		
Acid (H ₃ CCOOH) % max	0.05		

It is transparent glass solid light yellow granules, without any odor and taste, with good toughness and thermoplastic properties.

Usage:

- It is used as basic material of chewing gum, bubble gum

Packaging Storage and Transportation:

- 5kg per bag, 4 bags (20kg) per carton. Carton dimensions: 55cm x 35cm x 18cm or 55cm x 36cm x 15cm
- 6 cartons (120kg) per layer, 6 layers (720kg) per pallet
- 20 pallets (14400kg) per 20' Container

Katosan shall not be responsible for the use of this information, or of any product, method, or apparatus mentioned, and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of employees and purchasers of your products. No warranty is made of the merchantability of fitness of any product, and nothing herein waives any of the Seller's conditions of sale

Katosan Hong Kong Ltd.

Headquarter: 3806 Central Plaza, 18 Harbour Road, Wanchai, Hong Kong
Tel France : +33607871031

Certificate of Incorporation Number : 1801231